

# OV935WVA

Full Gigabit 5 Port Wireless AC VDSL2 Gateway



## Introduction

The OV935WVA is a high-speed dual-band Wireless G.fast Gateway, which is an advanced all-in-one gateway with G.fast and vdsl function. This product will be used in a Fiber To The Distribution set-up in which it must be able to interface to the Distribution Point Unit in the Wide Area Network via the latest ITU-T standard of G.fast. It can provide users with broadband Internet access capability, high quality voice & video services. OV935WVA is the solution that can provide gigabit speeds by using both copper and fiber

### System Spec

Chipset	BCM63138KFSBG(for 17A/G.fast)
Wi-Fi	BCM43602(2.4G 3T3R WiFi)-High power (20dBm)
11AC	BCM4366(5G 4T4R 11AC) –High power (20dBm)
DDR	DDR3-SDRAM,4Gbit
Flash	16MB Nor/128 MB NAND

### Interfaces

External Connectors	<ul style="list-style-type: none"><li>1xG.Fast SFP fiber port</li><li>1 x RJ11 interface for XDSL port</li><li>4 x RJ45 for Gigabit Ethernet LAN</li><li>1 x RJ45 for Gigabit Ethernet WAN</li><li>1 x Reset button for factory default settings</li><li>1 x 2.4G button for 2.4G WLAN and 2.4G WPS</li><li>1 x 5G 11ac button for 5G WLAN and 5G WPS</li><li>1 x USB3.0 &amp; 1xUSB2.0 Host port</li><li>1 x power jack</li><li>1 x power switch</li><li>Inner Antenna</li></ul>
---------------------	---

### Feature and Technical Spec

Wireless Features	<ul style="list-style-type: none"><li>Compatible with IEEE 802.11b, IEEE 802.11g, IEEE 802.11n and IEEE 802.11ac</li><li>3x3 MIMO @ 5GHz 3x3 MIMO @ 2.4GHz</li><li>Support beam forming to any 802.11 device</li><li>Support auto channeling</li><li>Support 64/128-bit WEP, 802.1x, WPA, and WPA2 for wireless security</li><li>Support eight SSID</li><li>Support RTS/CTS, Segment function</li><li>Support MAC Access/Deny List</li></ul>
Routing Features	<ul style="list-style-type: none"><li>Support IP routing</li><li>Support transparent bridging</li><li>Support source and destination routing</li><li>Support DHCP server/client</li><li>Support UPnP</li><li>Support NAT,NAPT</li><li>Support DMZ</li><li>Support IP QoS</li></ul>

### Feature and Technical Spec

#### Protocol Features

RFC 2684 multiprotocol Encapsulation over ATM Adaptation Layer 5  
 RFC2364 PPP over ATM ALL5 (PPPoA)  
 RFC2516 PPP Over Ethernet (PPPoE)  
 RFC1577/2225 Classical IP and ARP over ATM (IPoA)  
 MER (a.k.a IP over Ethernet over AAL5)  
 Support ALG (Application Level Gateways)  
 ITU G992.5 (ADSL2+)  
 ITU G993.2 (VDSL2)  
 ITU-T G9700/ G9701(Gfast)  
 IEEE802.3  
 IEEE 802.11n /11ac  
 Support ALG (Application Level Gateways)

#### G.fast Features

Support G.fast with crosstalk cancellation (vectoring) in DS  
 Support the full frequency band up to 106 MHz in G.fast  
 ITU-T G9700/ G9701(Gfast)  
 Support G.vector

#### Management

TR-069 Device Management  
 TR-098/181 Data Models  
 TR-106 Generic Device Model  
 TR-111 LAN Device  
 Management Device Configuration, Management and Update  
 Web based GUI  
 Command Line Interface via serial port, telnet  
 Universal Plug and Play (UPnP) Internet Gateway Device (IGDv1.0)

#### Security

Three-level login including local admin, local user, and remote technical support access  
 Service access control based on incoming interface: WAN or LAN  
 Service access control based on source IP addresses  
 Protect DOS attacks from WAN: SYN flooding, IP surfing, ping of Death, fragile, UDP ECHO (port 7), teardrop, land  
 PAP (RFC1334), CHAP (RFC1994), MSCHAP for PPP session  
 IP filter, Parental control

### Environment Requirements

Operating Temperature	0°C - 40°C (32F – 104F)
Storage Temperature	-10°C - 60°C (14F – 140F)
Operating Humidity	10% - 95%, non-condensing
Storage Humidity	5% - 95%, non-condensing
Power adapter input	100V - 240V AC, 50/60Hz
Power adapter output	12V DC, 3A

### EMC and Safety

Regulatory Compliance	CE、FCC、ROSH、CCC
-----------------------	-----------------

### Physical Characteristics

Physical Dimension	248mm*190mm*76mm
--------------------	------------------